

## LPR Plate Hotel

Under-the-Deck Integration Ideal for protein crystallization work Ideal for multiple cassette configuration





www.liconic.com Europe: Liconic AG, Liechtenstein Liconic UK Ltd, Manchester US & International: Liconic Inc, Woburn MA



## LPR 240

The LPR240 will hold up to 242 MTP with 23mm pitch. It is ideal for multiple cassette/sample configurations. The unit sits entirely under the workstation of liquid handler deck. Multiple transferstation can be used to increase production and throughput.

The LPR240 is ideal for protein crystallization work because the carousel can be stationary with the Star concept allowing the periscope the only moving part reducing vibration and movement of the samples. While allowing full remote access on handling, you are able to manually access the cassettes or samples from the front of the unit. For better access to cassettes located in the back of the instrument the carousel maybe positioned automatically or be rotated manually.

The LPR 240 with 242 MTP capacity makes it perfectly suitable for large integrations. Its compact size and its high capacity make it also ideal for mixed plates applications. Our various options make it ideal for many applications. For details please refer to www.liconic.com

| Capacity                |              |                        |  |  |  |
|-------------------------|--------------|------------------------|--|--|--|
| Plate Type              | Plate Height | Plate capacity of unit |  |  |  |
| NTP (Nanotiter Plates)  | 5 mm         | 462                    |  |  |  |
|                         | 11 mm        | 308                    |  |  |  |
| 1536                    | 12 mm        | 297                    |  |  |  |
| MTP (Microtiter Plates) | 17 mm        | 242                    |  |  |  |
|                         | 22 mm        | 187                    |  |  |  |
|                         | 23 mm        | 187                    |  |  |  |
|                         | 24 mm        | 187                    |  |  |  |
|                         | 27 mm        | 165                    |  |  |  |
| DWP (Deep Well Plates)  | 44 mm        | 110                    |  |  |  |
|                         | 53 mm        | 88                     |  |  |  |
| DiTi200                 | 66 mm        | 77                     |  |  |  |
| DiTi1000                | 104 mm       | 44                     |  |  |  |

|        | Order Nr.  | Options  |            |
|--------|------------|--|------------|
| LPR240 | 9143 01 35 |  | Order Nr.  |
|        |            | Bar Code Reader Option   | 9118 11 03 |
|        |            | Plate Presence Sensor / Optical detection of Plate in Cassette | 9121 00 62 |
|        |            | Disposal Tips upgrade kit up to 100mm height                   | 9118 12 23 |
|        |            | Fast access for time critical applications                     | 9111 10 00 |
|        |            | UCI Universal Communications Interface                         | 9118 11 17 |
|        |            | Housing  | 9143 01 36 |
|        |            | Linear Shaker, Amplitude 1-100mm, 12-300 rpm                   | 9143 02 01 |

## Accessories

|                   |  | Order Nr.  |
|-------------------|--|------------|
| Cassettes         | Inverted cassette MTP, 22 levels, pitch 23mm, all stainless steel                              | 9118 01 96 |
|                   | Inverted cassette Deep Well, 10 levels, pitch 50mm, all stainless steel                        | 9118 01 97 |
|                   | Inverted custom size cassette, nn levels, mm pitch (specify plate height), all stainless steel | 9118 12 32 |
| Transfer Stations | Standard transfer station plate with integrated plate detection sensor                         | 9147 00 24 |



